Certificate of Location of Government Corner

ID#: 511809 **Description:** SEC CEN 18 51 **Date Set:** **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

3"x7"x20" stone

Reference Ties:

The corner falls 1' west of north-south fence and in line with fence east
The monument is down 0.6'
This corner is located by GPS measurement

Corner History:

5-17-1875 Thomas Hunter, County Surveyor, (Book A, Page 276, Survey No. 273) set 3"x7"x20" stone at intersecting quarter lines. 1/16th West set 2"x9"x20" stone midway and on line at 19.70 chains (1300.20') to West 1/4 and not at government proration by request of parties involved.

12-11-1987 County Surveyor dug and found 3"x4"/11"x20" stone. The stone falls 1/2' west of corner post and in line with fences north, south and east. RP - CSD in corner post NE 1.08'

10-8-1999 Ed Kuisle, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Gave information to GGG. Computed center falls ± 0.75' south of stone found.

12-13-1999 GGG used computed center at intersecting quarter lines.

12-6-2011 County Survey Crew found 3"x7" stone down 0.6' in good condition and measured its position using GPS. Based on the county's section breakdown, the 3"x7" stone, as located by GPS in 2011, falls 0.82' north and 0.02' west of the computed center.