Certificate of Location of Government Corner

ID#:512005 **Description:** SEC COR 19 20 29 30 51 **Date Set:** 6/16/1976 **County:** Olmsted

Section: 20 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fences E-W-N
Post w/sign 1 1/2' NE
This corner is located by GPS measurement

Corner History:

8-1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 29 and 30. 80.00 Set post-corner to sections 19,20,29,30. Burr Oak 8 in. N68°W, 8 lks. Red Oak 4 in. S89-3/4°E, 172 lks. Burr Oak 7 in. S1°W, 565 lks.

11-1894 William Fraser (P.559 No.514) found a stone and tested it correct with the N.W. bearing tree.

6-1899 William Fraser (P.656 No.585) found the stone P.559.

1935 County Highway Department (B.81 P.37) measured South for 1 mile but did not describe this corner.

6-16-1976 County Surveyor found a 2"x15"x20" stone 1' South of a 2" pipe corner post to fences E-W-N. Set a C.I.M. over a 0.5"x18" rod as the corner and placed the stone on the South side of the C.I.M.

12-2-1987 County Surveyor found CIM in good condition.

11-13-2006 County Surveyor found CIM down 0.1' in good condition. Set sign & post 1.5' NE.