Certificate of Location of Government Corner

ID#:512105 **Description:** SEC COR 20 21 28 29 51 **Date Set:** 6/16/1976 **County:** Olmsted

Section: 21 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' south of E-W fence and 2' west of fence north
County Survey Disk in W side 12" Burr Oak N 96.13'
Post w/sign 2' north
This corner is located by GPS reference stations "Keefe C & D"

Corner History:

8-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 28 and 29. 80.00 chs. Set post corner to sections 20,21,28&29 Burr Oak 8 in. S82ºE 90 lks. Burr Oak 7 in. N60ºE 71 lks. Burr Oak 4 in. N501/2ºW 127 lks. Burr Oak 4 in. S54ºW 152 lks.

4-1878 Thomas Hunter (P. 337 No. 331), County Surveyor, found a stake and the N.E. and S.E. bearing trees standing. Set a new stake with a stone by its side.

4-1878 T. Hunter (P. 338 No. 332) found the corner P. 337.

6-1899 William Fraser (P. 656 No. 585), County Surveyor, found a large stone set by the side of the corner fence post with an old stake by its side. Tested the corner with the stump of the S.E. bearing tree.

6-16-1976 County Surveyor found a 2"x15"x24" limestone. Set a C.I.M. over a 1/2"x18" rod in place of the stone and placed the stone on the west side of the C.I.M.

5-21-1996 County Surveyor found CIM in good condition. SW of CP same as 1976 tie.

11-9-2006 County Surveyor found CIM down 0.2' in good condition. Monument now falls 3' south of E-W fence. Corner post has been replaced, Oak to the north there but did not try to locate CSD. Set sign & post 2' north.