Certificate of Location of Government Corner

ID#:512205 **Description:** SEC COR 21 22 27 28 51 **Date Set:** 7/12/1976 **County:** Olmsted

Section: 22 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and in line with fences east and west
County Survey Disk in PP #2315 SE 141.3'
County Survey Disk in CP W 33.46'
The corner is located by GPS measurement

Corner History:

8-1853 Gov't Notes: Willliam A. Jones, Deputy Surveyor. North between sections 27 and 28. 80.00 chs . Set post corner to sections 21,22,27,28. Aspen, 6 in., S6-1/2°E 435 lks . Aspen 6 in. S89°W 390 lks .

6-1872 Thomas Hunter (P.208 No.216), County Surveyor, states the corner missing. Accepted the location in the road and in line of an old fence avered by Mr. Cole as the corner.

4-1878 T. Hunter (P.337 No.331) found the stone set in a former survey.

4-1878 T. Hunter (P.338 No.332) found the corner P.337 .

7-7-1976 The County Surveyor dug across the entire surface of the road to clay with the backhoe but did not find anything.

7-12-1976 County Surveyor set a C.I.M. over a 0.5"x2' rod as the corner in the center of the N-S road and in line with the E-W fence.

11-9-2006 County Surveyor found CIM down 0.9' in good condition. Corner post to the east gone, other ties ok. 5/8" pipe with plastic cap RLS #21940 to the west but tree in line, can not take tie.