Certificate of Location of Government Corner

ID#:512305 **Description:** SEC COR 22 23 26 27 51 **Date Set:** 11/30/2004 **County:** Olmsted

Section: 23 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1/2' north of E-W fence
Traverse point "Ask B" N 5.32'
Post w/sign 2' west
This corner is located by GPS reference stations "Ask A & B"

Corner History:

Gov't notes: Set post and stone 12x12x3"

6-1872 Hunter pg 208 no 216 sec 27 found stake in mound 1/16 W - set stake 1/16 center NE1/4 sec 27 - set stake

6-1873 Hunter pg 230 no 233 sec 22-23 found stake in mound plain & visible. 1/16 N - set temporary point 1/16 E - set temporary point 1/16 W - set permanent stake

7-18-1985 County Surveyor found a 4.5" wood piece standing and down 16", which could be remain of stake in mound recorded by Hunter. Drove 2x2" hub at location of wood piece approx. 14.5' E and 0.45' north of T.N.

11-30-2004 County Surveyor dug for 2"x2" hub set at wood piece position in 1985. Found nothing. Set 6' telspar pipe driven to refusal with cast iron cap up 0.3' at computed wood piece position from GPS and traverse data.