Certificate of Location of Government Corner

ID#:512705 **Description:** SEC COR 27 28 33 34 51 **Date Set:** 8/28/1985 **County:** Olmsted

Section: 27 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 28' north of centerline of E-W twp road and 13' south of E-W fence
County Survey Disk in SE side brace post NE 17.17'
Punch hole in N end 14' CMP SSE 11.68'
Post w/sign 7' NE
This corner is located by GPS reference stations "Brevick A & B"

Corner History:

Gov't notes: Set sec corner post, 80 chs N. 12" White Oak, S3°W 510 lks. 15" White Oak, S47°W 410 lks.

4-1878 T. Hunter pg 337 no 331 found stake standing by side fence post. Claimed to be as where original stake stood. Bearing trees gone.

8-28-1985 County Surveyor set cast iron cap on telspar pipe as the corner at double distance from 1/4 line 28-33.

8-8-2006 County Suveyor found cast iron cap on telspar pipe up 0.6' on edge of runoff for culvert. Packed stone around monument and upstream. Set sign and post 7' NE of corner.

4-30-2007 County Surveyor found telspar pipe w/CIC up 0.3' in good condition.