Certificate of Location of Government Corner

ID#:512706 **Description:** 1/4 SEC COR 27 28 51 **Date Set:** 6/4/1996 **County:** Olmsted

Section: 27 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 30' east of cattle panel yard fence north and 1' south of E-W fence
Pipe with cap W 96.5'
Post w/sign 1' north
This corner is located by GPS reference stations "Norb A & B"

Corner History:

Gov't notes: Set 1/4-sec-post, 40 chs. 5" Aspen, N86ºW 45 lks. 5" Aspen, S55-1/2ºE 19 lks.

6-1872 T. Hunter pg 208 no 216 found original stake standing. Tested and found correct. Set new stake. 1/16 N - set stake

4-1878 T. Hunter pg 337 no 331 1/16 W - set temp stake 1/16 N - found stake pg 208 but set new stake

7-9-1985 County Surveyor found a piece of an old stake lying flat and under a few inches of soil. Could not find Aspen BT. Shot E-W-fence line. Dug and found black mark in clay but nothing further.

6-4-1996 County Surveyor, matching 1/16 fence N we found a mark of a post, dug down 2.5' feet through rock. The post mark is 1' S of line of E-W-fence. Drove 5' long cast iron cap on telspar pipe to resistance as corner. Set post and sign 1' N in fence line.

11-13-2006 County Surveyor found telspar pipe w/CIC up 0.5' in good condition.