Certificate of Location of Government Corner

ID#:512904 **Description:** 1/4 SEC COR 29 32 51 **Date Set:** 7/2/1976 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 22' NE of centerline of twp road on curve and 30' north of centerline of driveway east
Top center TCM box NE 73.43'
Center of CP E 35.2'
W flange of telephone box SW 72.9'
Post w/sign 30 1/2' E
This corner is located by GPS measurement

Corner History:

8-1853 Gov't Notes: William A.Jones, Deputy Surveyor West on true line between sections 29 and 32. 40.05 chs. Set a quarter section post. White Oak 8 in. N51°W, 62 lks. White Oak 10 in. N57°E 161 lks. 80.10 chs. Intersect at the section corner.

6-1857 Thomas Hunter (P.33 No.29), County Surveyor, used the corner to set the Center of Sec. 29.

12-1886 T. Hunter (P.418 No.407) used the line of the fence South for the E-W location of the corner.

1938 John Kerr (B.12 P.51 and Co.Hwy.Dept. B.104 P.6) set a drill steel as the corner midway and on line.

6-30-1976 County Surveyor dug with the backhoe at the midway and on line location but did not find anything.

7-2-l976 County Surveyor set a C.I.M. over a 0.5"x25" rod as the corner midway between the section corners and in line with the main line of the fence East.

2-14-2005 County Surveyor found CIM in good condition down 0.9' along east shoulder of 155th Ave SE. Monument falls inline w/fence east and 4' east of extended line of fence north. Did not check ties. Set sign and post 30 1/2' east.