Certificate of Location of Government Corner

ID#:512905 **Description:** SEC COR 29 30 31 32 51 **Date Set:** 3/14/2005 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in line with fence west and 15' east of N-S fence
County Survey Disk in S side CP W 17.42'
County Survey Disk in NW side blazed 24" Burr Oak NE 88.76'
Post w/sign 2' north
This corner is located by GPS reference stations "Bicknese A & B"

Corner History:

8-1853 Gov.Notes: William A. Jones, Deputy Surveyor. North between sections 31 and 32. 80.00 chs. Set post corner to sections 29,30,31&32. Burr Oak 10 in. N14°E 126 lks. Burr Oak 6 in. N89ºW 238 lks. Burr Oak 8 in. S3-1/2°E 196 lks. Burr Oak 8 in. S3-1/2ºW 227 lks.

4-19-1878 Thomas Hunter (Old Field Book #5 No.330-1/2), County Surveyor, found the remains of the old stake in the ground. Set a stone in its place.

11-1894 William Fraser (P.559 No.514), County Surveyor, found the stone set by Hunter.

5-1901 William Fraser (P.12B) found stone.

7-1936 county highway department (B.81 P.37) found old stake.

3-1938 John Kerr (B.12 P.51), County Surveyor, found stake. Set a drill rod with a boulder over the top.

1964 county highway department (B.295) found stone.

6-1973 Sankstone & Taylor found a 1" steel rod under a boulder.

6-29-1976 County Surveyor found a drill steel under a boulder as recorded. Accepted the drill steel as the corner. Removed the boulder and drove a light 1-1/4"x26" pipe over the drill steel (up 4"). Put the boulder alongside the pipe.

8-29-2003 County Surveyor found piece of drill steel up 0.3' leaning SW.

2-11-2005 County Surveyor found drill steel leaning SSW. All ties gone except spike in NW side of blazed oak which was grown over but still there.

3-14-2005 County Surveyor removed drill steel and set 5' telspar w/CIC from computed coordinates up 0.8' CSD w/conc nail in south side of corner post west 17.42'. CSD w/conc nail over spike in NW side of blazed 24" Burr Oak NE 88.76'. Set sign and post 2.0' north.