Certificate of Location of Government Corner

ID#:512906 **Description:** 1/4 SEC COR 29 30 51 **Date Set:** 2/22/2005 **County:** Olmsted

Section: 29 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 15 1/2' north of fence west and in line with fence south
County Survey Disk in CP S 15.48'
Post w/sign 2' north
This corner is located by GPS measurement

Corner History:

Gov't notes: Set 1/4-sec-post, 40 chs. 8" White Oak, E 58 lks. 16" Burr Oak, N 650 lks.

6-1857 T. Hunter pg 33 no 52 used original corner to set center - measured E 39.90 chs.

11-1894 W.Fraser pg 559 no 514 found marked stake set by T. Hunter in unrecorded survey of 4-19-1878 drove new stake with 2 stones by side of stake. Hunter's measure S to sec corner 39.93 chs. Fraser's measure S to sec corner 39.96 chs.

6-16-1976 County Surveyor found black spot in clay 15' N of corner post to fence ..... and in line of fence W. Put 1/2"x18"-rod in mark. Pieces of limestone found around mark.

4-2-1993 McGhie's apparently used 1/2"-rod for survey in sec 30 (# 5130-6, 1983). May be final considering location with fences and old measure S.

2-22-2005 County Surveyor found 1/2" rerod down 0.4' in good condition. Set 4' telspar pipe w/CIC over iron rod at surface. CSD in CP south 15.48'. Set sign and post 2.0' north.