Certificate of Location of Government Corner

ID#:513005 **Description:** W SEC COR 30 31 51 **Date Set:** 7/13/1977 **County:** Olmsted

Section: 30 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

County Survey Disk in SE post for snowmobile bridge NE 124.41'
Post w/sign 36' east
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 31 and 36. 76.60 chs. Brook 4 lks. wide runs S.W. 80.00 chs. Set corner post and drove charred stake. Built mound with trench and planted osage orange seed S.E. and apple seed N.E.

4-1878 Thomas Hunter (Book A. P. 336 No. 330), County Surveyor, "at M (W. 30-31)-Found original stake driven well down at corner of fence." Set a stake at the 1/16th North.

9-1881 T. Hunter (Old Field Book 5 P. 124) used this corner to set the W. 1/4 Cor. 31 midway and on line.

5-1901 William Fraser (Book B P. 12) used the corner post of the fence as the corner to set 1/4 Cor. 30-31.

11-7-1968 John Kerr (Kerr Book 101 P. 31-certificate filed), County Surveyor, found remains of stake with limestone by its side down 36" and old wire running N-S-E&W. Placed stub of steel fence post by stone and placed a C.I.M. over the stone. Put a 2" pipe North of the corner sticking above ground. Found this corner by doubling the line and measure from the S.W. Cor. 31 over the fence corner at the W. 1/4 Cor. 31.

7-13-1977 Mn/DOT found Kerr's C.I.M. and took references.

4-11-1991 County Survey Crew set post and sign 1' west of CIM

2-11-2005 County Surveyor found CIM in good condition down 0.6' in cultivated field. All old ties are gone as well as willow tree. CSD in SE post for snowmobile bridge NE 124.41. Set sign and post 36' east on top bank for stream.