Certificate of Location of Government Corner

ID#:513106 **Description:** W 1/4 SEC COR 31 51 **Date Set:** 11/25/1968 **County:** Olmsted

Section: 31 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fence east, 2' west of fence north and 2' south of fence west
Steel fence post 1/2' south
Sign on CP 1 1/2' ENE
This corner is located by GPS measurement

Corner History:

Oct. 1853 Gov't Notes Ball, Deputy Surveyor North between 31 and 36. 33.68 White Oak 10". 40.00 Set quarter section corner. Aspen 10", S88W 22 lks. Aspen 10", S50E 13 lks. 51.36 Aspen 14" 64.90 Brook 20 lks. wide runs S.E.

5-1886 T. Hunter Pg.405 No.394 found corner fence post set as corner.

5-1901 W. Fraser book B pg.12. Used corner fence post.

11-1902 W. Fraser book B pg.40. Used corner post placed by T. Hunter.

11-25-1968 J. Kerr found corner post as described in surveyors record. Set CIM in place of post.

9-25-1969 J. Kerr found pipe in center of old railbed (rails now gone) set by McGhie crew on exact line. CIM and center sec 31 as set at present.

2-10-2005 County Surveyor found CIM in good condition down 0.5'. Monument falls inline with fence east and 2.0' west of fence north and 2.0' south of fence west. Set sign on large corner post 1.5' ENE.