# Certificate of Location of Government Corner

**ID#:** 513205 **Description:** S SEC COR 31 32 51 **Date Set:** 8/28/2003 **County:** Olmsted

**Section:** 32 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

County Survey Disk in 18" Walnut NW 27.87'
County Survey Disk in 30" Oak SSE 30.27'
Post w/sign 2' west
This corner is located by GPS measurement

**Corner History:**

9-1853 Gov't notes: Set post for corner & built mound of rock.

12-24-1886 T. Hunter pg 418 no 407 sec 32 found corner gone. Set stake carefully M&L between S1/4-corner sec 32 and S1/4-corner sec 31. 1/16 E - set stake 1/64 E - set stake 1/16 N - set stake

3-1938 J.Kerr Bk 12 pg 51 sec 32 County Hwy. Dept.set or found iron bar as corner. Measure N to 1/4-stone 2634.0'. 1/16 E - found pin

6-1973 Sankstone & Taylor found iron bar (3/4 x 1") up 6" - 2' West of N-S-fence. Meas. N to 1/4-cor (limestone), 2629.18' E.T.C.; meas. W to 1/4-cor of sec 31 (brass plate) 2639.38' E.T.C. 1/16 (W?) - found 2" cap

2-1975 Fillmore County Surveyor found a 1' square iron. Fillmore County Certificate of Location Doc. No. 372133

9-1-1984 Olmsted County Surveyor visited and found shaft as described. Took no more references.

8-28-2003 Olmsted County Surveyor found 3/4" bar up 0.4'. Took local ties and removed. Set CIC on 3.0' telspar pipe up 0.2'.

2-9-2005 Olmsted County Surveyor found telspar pipe w/CIC in good condition up 0.1'. Did not check ties.