Certificate of Location of Government Corner

ID#:513206 **Description:** 1/4 SEC COR 31 32 51 **Date Set:** 11/17/2005 **County:** Olmsted

Section: 32 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls under N-S fence and 25' south of south bank of creek
Post w/sign 2' west
This corner is located by GPS reference stations "Gully A & B"

Corner History:

Gov't notes: Set 1/4-sec-post, M&L 40 chs.

12-1886 T. Hunter pg 418 no 407 (Field Book 14, pg 78) found stone as corner. 1/16 S - set stake

5-1901 W.Fraser pg 12 "B" found stone and stake set as corner.

3-1932 J.Kerr Bk 12 pg 51 for County Hwy. Dept. found stone. 2636.4' N, 2634.0' S. 12" Ash, SE 28.8'.

1936 county highway department Bk 81 (pg 37) & 104 found limestone 2x12x18" up 6". Small limestones on either side.

1964 county highway department Bk 295 found limestone in gully area. Measure N 2637.46'. 1599.87' N to center road.

6-1973 Sankstone and Taylor found limestone (up 3") set 0.5"x2' pipe on W side. 2636.24' N to sec-cor. 2629.18' S to sec-cor. 2641.95' W to existing center-sec-cor.

2-18-2005 County Surveyor found 2"x12" stone down 0.1' with 1/2" pipe on east side in good condition.

11-17-2005 County Surveyor removed 2x8x12 stone with 1/2" pipe along east side. Set 3' telspar with CIC up 0.3' at stone location. Set sign & post 2.0' west.