Certificate of Location of Government Corner

ID#: 513304 **Description:** S 1/4 SEC COR 33 51 **Date Set:** 9/16/1975 **County:** Olmsted

Section: 33 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 2.5'
The corner falls 3 1/2' north of E-W fence
County Survey Disk in N side brace post (most easterly post) W 105.4'
1/2" Pipe w/cap #15229 E 98.69'
Post with sign, south 5'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes 40.00 chs. West on south boundary of section 33. Set quarter section post and built mound with trench as per instructions. Drove charred stake in center and planted osage orange seed in N.W. corner.

Found no other record on this corner.

4-1878 E. Tuohy sec 33 see T.H. Book 5 pg.60 at "F" found stake marked said to have been set by county surveyor of Fillmor Co. found it on line and midway between "E" -"G". Meas east 19.92-1/2 then 19.92-1/2 to SE 33. Meas west 19.92 then 19.92 then 19.92 to SW 33. Meas north 19.98-1/2 then 19.98-1/2 to cen 33 at center of SW 1/4 at "12" set stone 20x9x3 at center of SE 1/4 at "14" set stone 22x4x3 at "13" 1/16 cor north between S 1/4 33 and cen 33 set stone 23x7x4.

9-16-1975 Olmsted County Surveyor corner lies near creek in area of much erosion. Set C.I.M. over 1"x19" rod deep to avoid washing out. Corner set midway and on line from S. Sec. Cor. 32-33 to S. Sec. Cor. 33-34.

9-16-1975 Fillmore County Certificate of Location Doc. No. 372129

7-30-1985 Olmsted County Surveyor took tie to 1/2" pipe w/cap #15229 east 98.69'

4-5-2011 Olmsted County survey crew found CIM in good condition.