Certificate of Location of Government Corner

ID#: 513604 **Description:** S 1/4 SEC COR 36 51 **Date Set:** 6/25/2004 **County:** Olmsted

Section: 36 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

60d spike in W side Oak S 30.85'
County Survey Disk in N side of forked blazed 14" Burr Oak SW 81.11'
Sign on CP 1/2' north
This corner is located by GPS reference stations "Sass C & D"

Corner History:

1853 Gov't Notes West on the south boundary of section 35. 40.00 chs. Intersect corner to Township 104 North of Ranges 10 and 11 West 5th Meridian and used it for quarter section corner.

9-12-1975 Olmsted County Surveyor found 6" square iron plate reading: "S,1 T104 R11". Plate on 2" square shaft on S. side of new corner post to fences N-S-E and on N. side of old corner post.

9-12-1975 Fillmore County Certificate of Location Doc. No. 372126

6-7-2004 Olmsted County Surveyor found 6" square iron plate down 1.5' leaning to the west.

6-25-2004 Olmsted County Surveyor removed 6"x6" iron plate. Set 5' cast iron cap on telspar pipe up 0.2' from GPS and traverse data.