# Certificate of Location of Government Corner

**ID#:**520105 **Description:** SEC COR 1 2 11 12 52 **Date Set:** 9/1/1988 **County:** Olmsted

**Section:** 01 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The monument is at the surface
The corner falls 74' east of centerline of creek
County Survey Disk in 9" Burr Oak S 50.32'
This corner is located by GPS measurement

**Corner History:**

9-1853 Gov't Notes 80.00 Ch. Set post Bearing trees Br. Oak 14" S 1 3/4deg.W 295 lks. Br. Oak 6" S 26deg. E 180 lks.

4-1856 Tom Hunter P. 13 No. 20 Used Corner 1/16 E 19.83 M&L

2-1867 H. Horton P. 82 No. 123 Used Corner 1/16E 20.02 M&L. 1/16S 20.00 M&L.

5-1877 Tom Hunter P. 311 No. 305 Found original corner and tested bearing tree stumps. 1/16 S. Set stone 2x10x37 M&L 20.07 3/4. 1/16 Center NE 1/4 11 - Drove stake 19.93 1/2 M&L on E-W 1/16 line.

5-1903 Armstrong P. 50 B Found stone at 1/16 Cor. S.

6-12-1988 County Surveyor 1/16 corner south sec cor 1, 2, 11, 12 105-12 found recorded stone 2x10x37 on E side of RR.

7-29-1988 County Surveyor dug at computed location of cor. Found nothing.

8-4-1988 County Surveyor dug additional 5' off east side of digging (found nothing)

9-1-1988 County Surveyor set cast iron cap on telspar pipe on line and proportinate mesure from sec. Cor 11, 12, 13, 14 over the 1/16 stone south of this sec cor. Found.

8-2-2011 County survey crew found cast iron cap in good condition