Certificate of Location of Government Corner

ID#:520204 **Description:** 1/4 SEC COR 2 11 52 **Date Set:** 9/1/1992 **County:** Olmsted

Section: 02 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is up 0.3'
The corner falls in line with fence north and 3' south of E-W fence
County Survey Disk in CP N 2.86'
County Survey Disk in brace post ENE 7.93'
Sign on CP 2 1/2' north
The monument is located by GPS measurement

Corner History:

10-6-1853 Gov't Notes West on True Line between Sections 2 + 11 Var 9deg.40'E 39.95' Set Qr. Section Post Br. Oak 6" S611/2degE 29 lks. W. Oak 13" N42degW 50 lks.

5-1877 Tom Hunter P.311 No. 305 Corner gone - B trees disagree in bearings. Used fence post as corner. 1/16 S. set stone 6x9x17 M&L 20.08' 1/16 Center NE 1/4 - Sec. 11 set stake 19.93' 1/2 M&L E-W 1/16 line.

9-1-1992 County Surveyor dug for corner post used by T.H. in 1877 - Found 10" sq. black mark bottom at 3'deep with wood (wire & staples in it. Set cast iron cap on telspar pipe at post mark location. Corner falls in line of fence N. & 3' S. of main line E-W fence.

8-2-2011 County survey crew found cast iron cap in good condition