Certificate of Location of Government Corner

ID#:520504 **Description:** 1//4 SEC COR 5 8 52 **Date Set:** 4/21/1977 **County:** Olmsted

Section: 05 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' north of centerline of E-W twp road and 5' west of fence south
Top center TCM box N 25.1'
County Survey Disk in S side PP #44410 ENE 149.25'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 5 and 8. 39.91 chs. Set post-quarter section corner. Burr Oak 8 in. S78ºW 108 lks. Burr Oak 9 in. N61ºW 113 lks. 79.82 chs. To section corner.

6-1891 Thomas Fraser (P. 436), County Surveyor, found the stake and the SW bearing tree. Set the 1/16th South, the Center 8, and the S 1/4 corner 8. Note: According to Fraser's Old Field Book 7 P. 101 it was the 1/16th South of the Center 8 he actually set and not the 1/16 North of the Center 8.

4-1968 John Kerr, County Surveyor, found the Center 8 and found a stone lying on the ground by a large corner post at the 1/16th North. Doubled the line and measure from the Center 8 over the stone found at the 1/16th North and set a pipe as the corner.

9-1968 John Kerr set a CIM in place of the pipe set on 4-1968.

4-1977 County Surveyor dug on line from the S 1/4 corner 8 (found) over the Center 8. Found a square mark with wood pieces in clay 2' deep. Accepted this as the location of the stake recorded by Fraser. Set a CIM over a 5/8x13" iron as the corner 5.13' West and 9.42' South of Kerr's CIM (removed).

9-13-1979 County Surveyor at 1/16 east: Set a 5/8"x17" iron M&L. Corner is 5' south E-W road and 3' east centerline N-S road. RP's - county highway department disc NW side PP #20727 N-E 46.65', county highway department disc south side PP #20726 NW 56.90'.

5-5-2009 County Surveyor found CIM down 0.5' in good condition.