Certificate of Location of Government Corner

ID#:520505 **Description:** SEC COR 5 6 7 8 52 **Date Set:** 6/27/1968 **County:** Olmsted

Section: 05 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 2' north of centerline of E-W twp road
Nail in W side witness tree S26ºE 38.85'
Tele bell top center by PP NW 43.5'
County highway disk in PP #16490 SE 42.4'
This corner is located by GPS measurement

Corner History:

10-6-1853 Gov't Notes William Jones North between sections 7&8 80.00 chs. Set post corner to sect. 5-6-7-8 Burr Oak 8 S 21 W 127 Burr Oak 8 S 12 E 115 Burr Oak 6 N 62 E 54 Burr Oak 5 N 72 W 64

7-1876 T. Hunter P. 302 No. 297 Corner stake accepted. Measure north 39.96' line & prop. Meas. Then 38.01' to town line.

11-1877 T. Hunter P. 325 No. 319 Found stake P. 302 set stone 25"x3"x20" Meas. So. 39.92' Meas. West 39.97'

4-1909 C. Armstrong P. 118 B Found stone P. 325 Burr Oak 15" S26ºE 48 lks. Meas. So. 39.90' to limestone found.

4-26-1968 J. Kerr dug extensively, will dig again at W1/4 8 further west.

4-27-1968 J. Kerr rerun and meas. Entire mile after finding 1/4 7-8 found bottom half recorded stone in good shape. Meas. So. To 1/4 cor. Found 2633.0' then 2633.4' to sec. cor.

6-27-1968 John Kerr found bottom half of recorded stone. Set CIM over sash weight and stone pieces.

10-18-2004 County Surveyor found CIM down 1.1' in good condition.