Certificate of Location of Government Corner

ID#:520506 **Description:** 1/4 SEC COR 5 6 52 **Date Set:** 9/11/1968 **County:** Olmsted

Section: 05 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' east of centerline of N-S twp road
County Survey Disk in S side PP #16480 E 28.05'
This corner is located by GPS measurement

Corner History:

10-6-1853 Gov't. Notes 59'E on true line between sections 5&6 Var 10º 29'E 38.05' Set post at gr. Section corner. 78.05' To section corner.

7-1876 Hunter P. 302 No. 297 Corner gone. Placed non-described corner at 38.01' No. 39.96' so. (no bearing) Meas. West 39.87' S891/2ºW to stake set as center.

9-1968 J. Kerr run line from NE 6 to SE 6 5144.07 Set C.I.M. on line at 2507.77' then 2636.3. Corner lies 3.5' east of centerline traveled road N-S. Corner lies with fence running west. Corner lines 3' south fence running east. Disc in power pole #16980 East 27.9' Pipe cap in tele. Pole SSW 103.4'

4-1-1977 County Surveyor dug down to Kerr' C.I.M. with the jackhammer. Set C.I.M. over and up to surface. Corner 4' E. of centerline N-S road and (see Pat) (Co. Surveyor wants to dig before final acceptance).

10-18-2004 County Surveyor found CIM down 0.3' in good condition.