Certificate of Location of Government Corner

ID#:520604 **Description:** 1/4 SEC COR 6 7 52 **Date Set:** 4/20/1977 **County:** Olmsted

Section: 06 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 17' south of centerline of E-W twp road and 6' east of fence south
County Survey Disk in E side PP #11666 SSW 22.30'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor East of true line between sections 6 and 7. 39.21 chs. Set post for quarter section corner. Burr Oak 8 in. N81/2ºE 225 lks. Burr Oak 7 in. S8ºW 154 lks. 79.21 chs. To Section Corner. Measured South on West side of Section 7. Find length of mile only 79.10 and find that corner to sections 7,12,13&18 and to 1,6,7&12 have been established South of original measurement.

7-1876 Thomas Hunter (P. 302 No. 297), County Surveyor, found the stake remains. Set a stake at the 1/16th West on line and at proportionate measure.

11-1877 Thomas Hunter (P. 325 No. 319) found the stake P. 302. Set a 21/2"x4"/ 16"x23" stone as the corner.

1968 John Kerr, County Surveyor, dug with the backhoe on the North half of the E-W road and in line with the fence South. Found nothing.

7-1-1969 John Kerr dug the South half of the road. Found nothing.

7-3-1969 John Kerr set a CIM as the corner on the line between the section corners and at proprated Hunter measure.

4-20-1977 County Surveyor dug from Kerr's CIM South. Found Hunter's recorded stone 12.4' South and 2.3' East of Kerr's C.I.M. (removed). Set an iron on the East side of the stone and set a Cast Iron Cap on a square pipe up to the surface as the corner.

10-18-2004 County Surveyor found cast iron cap on telspar pipe down 1' in good condition.