Certificate of Location of Government Corner

ID#:520704 **Description:** 1/4 SEC 7 18 52 **Date Set:** 4/27/1977 **County:** Olmsted

Section: 07 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is down 0.3'
The corner falls on steep hillside 15' north of center of deep ditch and 25' south of centerline of old road
Spike in N side 4" Elm W 5.09'
Spike in W side 3" Maple S 5.12'
County Survey Disk in SE side blazed Red Oak SW 90.55'
County Survey Disk in SW side 18" blazed Red Oak SE 55.96'
Post with sign, Northwest 0.5'
This corner is located by GPS reference stations

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor East on true line between sections 7 and 18. 39.50 chs. Set quarter section post. Burr Oak 10 in. N3ºW 83 lks. Red Oak 13 in. South 105 lks. 79.50 chs. To section corner.

11-1877 Thomas Hunter (P. 325 No. 319), County Surveyor, reset a stake from the N.W. bearing tree found standing. Set the 1/16th North, the Center 7 and the N. 1/4 Cor. 7.

5-1878 T. Hunter (P. 345 No. 338) found the stake set P. 325. Set that stake in place of the stub of the original stake now found 3 lks. East.

4-27-1977 County Surveyor set a CIC on a square pipe as the corner on the line from the N. 1/4 Cor. 7 (found) over the Center 7 (found by John Kerr) and at double the measure from the Center 7 over the E-W fence at the 1/16th South. This corner comes on a steep hill covered with stone from an old road cut into the sidehill 25' North. Drove a steel fence post on the West side of the CIC.

7-28-2011 County survey crew found cast iron cap on telspar pipe in good condition.