Certificate of Location of Government Corner

ID#:520705 **Description:** W SEC COR 7 18 52 **Date Set:** 4/26/1977 **County:** Olmsted

Section: 07 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls on the north bank edge of an overflow and high water channel for the Root River and 380'± North of the north bank of the river and 36' south of an old fence and posts
County Survey Disk in NE side 31" blazed Elm NW 6.64' (possible bearing tree)
County Survey Disk in NW side 24" blazed Elm NE 19.68'
County Survey Disk in 5" soft Maple SW 29.18'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 13 and 18. 73.10 chs. Stream North fork of Root River 125 lks. Wide runs East. 80.00 chs. Set corner post. Elm 14 in. S44ºE 15 lks. Sugar 10 in. S65ºW 24 lks. Dug trench.

1-1876 Thomas Hunter, County Surveyor, (addition to P. 239 No. 241 and Field Book 4 P. 98) found the original stake standing on the North edge of the slough or pond. Tested with the bearing trees and also took a bearing tree: 6" W. Elm N57ºW 10 lks.

5-1878 T. Hunter (P. 345 No. 338) found the original stake and both bearing trees. The corner stands at the North edge of the water by the side of the river.

5-5-1975 County Surveyor found a huge Elm standing on the North bank of a pond on the North side of the river. Set an iron rod at Hunter's bearing and distance as taken in 1876.

4-26-1977 County Surveyor set Cast Iron Cap on a square pipe driven over the rod set in 1975 as the corner. The corner came 380' North of the North bank of the Root River.

11-5-2009 County Surveyor found cast iron cap on telspar pipe up 0.4' in good condition.