Certificate of Location of Government Corner

ID#: 520709 **Description:** SEC CEN 7 52 **Date Set:** 9/24/1968 **County:** Olmsted

Section: 07 **Township:** 105N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Cast Iron Monument

Reference Ties:

The corner falls 1' east and 1' north of wooden corner post for fences east and south
The monument is down 0.4'
Center of 24" Red Oak ESE 17.25'
Center of 18" Burr Oak SSE 20.0'
This corner is located by GPS measurement

Corner History:

11-15-1877 Thomas Hunter, County Surveyor, (Book A, Page 325, Survey No. 319) set 2"x16"/24"x34" stone at intersecting quarter lines. 1/16th South set stake midway and on line at 19.99-1/2 chains (1319.67') to South 1/4.

9-24-1968 John Kerr, County Surveyor, found all but tip of huge stone described standing vertical in clean soil just west of corner post in line with fence east. Set Cast Iron Monument over 5/8"x20" rod with large pieces of stone on north, south, and west sides. RPs - Center 24" Red Oak ESE 17.25', Center 18" Burr Oak SSE 20.0'

8-1-2011 County Survey Crew found Cast Iron Monument down 0.4' in good condition and measured its position using GPS.

9-21-2018 Mark Severtson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the Cast Iron Monument, as located by GPS in 2011, falls 0.16' north and 0.05' west of the computed center.