Certificate of Location of Government Corner

ID#:520805 **Description:** SEC COR 7 8 17 18 52 **Date Set:** 4/26/1968 **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is at the surface.
The corner falls under fence north and 8' north of E-W fence and 1' north of brace post
Bed rail up 3' east of monument
20" Burr Oak S 2° E 31.7'
This corner is located by GPS measurement

Corner History:

10-6-1853 Gov't Notes, William Jones North between sections 17&18 80.00 chs. Set post corner to sect. 7-8-17-18 Burr Oak 4 5 54 W 95 Burr Oak 3 N 56 E 13 Burr Oak 4 S 50 E 136 and dug trench.

11-1877 T. Hunter P. 325 No. 319 Found orig. stake by fence corner, Bearing trees all cut. Left corner as is. 1/16 north set stake M&L 19.96'.

6-1891 T. Fraser P. 452 No. 436 Found above stake P. 325 Meas. East 2638.3' to stake set M&L

6-1902 R. Fraser P. 710 No. 624 Found nail and small stone pieces set by Sidney Burnap. Drove stake and set stone M&L 20.00 13/116 - 1320.8 1/16 east drove stake 20.001/4 M&L to 1/4 stone.

4-1909 Armstrong P. 116B Found iron bolt as corner. Bearing trees 10" Burr Oak N 89º E 72 lks. 6" Burr Oak S 2º E 48 lks. Meas. 39.88' no. S2'W to recorded limestone found.

4-26-1968 J. Kerr found iron bolt & limestones in place. Drove bolt 2' deep set C.I.M. on top. Set bed rail up 3' east of mon. 20" Burr Oak S2ºE 31.7' fence line north east 2.4' - fence line west south 8.0'.

2-28-2011 County survey crew found CIM in good condition.