Certificate of Location of Government Corner

ID#: 520809 **Description:** SEC CEN 8 52 **Date Set:** 6/24/1891 **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Stone

Reference Ties:

The corner falls in line with fence north and 1' north of fence west
The stone is down 0.5'
This corner is located by GPS measurement

Corner History:

3-21-1879 Thomas Hunter, County Surveyor, (Old Field Book #5, Page 94), unrecorded survey, set stake at intersecting quarter lines. 1/16th South set stake midway and on line at 20.02-1/2 chains (1321.65') to South 1/4.

6-24-1891 Thomas Fraser, County Surveyor, (Book A, Page 452, Survey No. 436 and Old Field Book #7, Pages 99-101) set 5"x6"x20" stone on top of boulder at intersecting quarter lines. 1/16th North set stone midway and on line to North 1/4. 1/16th South set stake midway and on line to South 1/4. 1/16th West set stone midway and on line to West 1/4.

4-22-1968 John Kerr, County Surveyor, found pointed stone over boulder and set Cast Iron Monument. The corner falls in line with fence north and 2' north of fence west. RP - 20d nail in West side 6" box elder SSE 38.75'. 1/16th West found 6"x6"x18" stone. Set 3/4"x24" pipe on south side and sash weight on north side.

2-28-2011 County Survey Crew found Cast Iron Monument pulled out and leaning against corner post.

7-27-2011 County Survey Crew found pointed stone down 0.5' in good condition and measured its position using GPS.

4-30-2018 Mark Severtson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the stone monument, as located by GPS in 2011, falls 0.86' south of the computed center.