Certificate of Location of Government Corner

ID#:521005 **Description:** SEC COR 9 10 15 16 52 **Date Set:** 7/25/2011 **County:** Olmsted

Section: 10 **Township:** 105N **Range:** 12W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is up 0.1'
The corner falls 1' south of fence east and in line with fence north
This corner is located by GPS reference stations "Big Buck A & B"

Corner History:

10-6-1853 Gov't Notes - William Jones 80.00 chs. Set post corner to section 9-10-15-16 Burr Oak 6N381/2 W 171 Burr Oak 6S261/2 E 246 White Oak 8S14W 228 White Oak 8N5 W 272 North between sections 15&16 VAR 9º35'E

1891 T. Fraser Old Fieldbook (7) pg. 99-101Found large boulder to be placed on orig. mound by Fisher & others 2 mi. West short 6'10".

5-1903 Armstrong P. 50B Used corner to set NW cor. 14 by prop. Meas. Plat say 40.02' west and 39.81' east of NW1/4 actually J proves 39.81' (2627.5') is correct. No desc. Of corner.

1941 county highway department (Archie) B. 127 P.4 Found old stake &stone 2' east of fence corner. Ran N-S sec. line set 1/4 15-16 M&L 2622.4'±.

7-13-62 J.Kerr B85 P. 60 Run north line 15 found 1" pipe 1.0' north 4" iron pipe c.p. Meas. East to 1/4 C.I.M. 2626.5'±.

3-31-1980 County Surveyor found 1" iron pipe on N side of 5" dia. Iron c.p. and a wood c.p. is ± 11/2' N. of pipe ± 2' dia. Boulder is lying ea. Of 1" pipe. 30" Oak - 130' East (W. one-half of Twin Oaks)

12-14-1990 V. Fangman found and used 1" pipe as corner for survey in SE 1/4 section 9-105-12.

11-11-1998 GGG found and used pipe as corner for survey in NW 1/4 section 15-105-12.

12-8-1998 County Surveyor found 1" pipe in good condition.

3-5-2003 GGG, Inc. found and used pipe as corner for survey in SE 1/4 section 9-105-12.

12-18-2007 County survey crew found 1" pipe up 0.4'.

7-25-2011 County survey crew found 1" pipe. Removed and replaced with a 4' telspar pipe with cast iron cap.