Certificate of Location of Government Corner

ID#:521104 **Description:** 1/4 SEC COR 11 14 52 **Date Set:** 9/28/1978 **County:** Olmsted

Section: 11 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.3'
CIC on sq. pipe: Reference Pt. (Survey marker sign) NE 62.95'
The corner falls 57' south of E-W fence
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 11 and 14. 39.97 chs. Set quarter section post. Burr Oak 8 in. N861/2ºE 200 lks. Burr Oak 8 in. S71ºE 167 lks.

5-1877 Thomas Hunter (Book A P. 311 No. 305), County Surveyor, found stake remains avered by a George Hopkins as the site of the original stake. Set a stone 5"x8"x27" in its place. Set a 7"x6"x30" stone at the 1/16th North, a 3"x6"/10"x16" stone at the Center 11, and a 6"x9"x17" stone at the 1/16th North of the Center 11.

5-1903 C. Armstrong (P. 50 Book B), County Surveyor, set a stone midway and on line between the section corners after resetting both section corners. Set a stone at the 1/16th North and an iron at a property corner approx. 9.95 chs. East.

8-28-1978 County Surveyor found Hunter's recorded stone at the 1/16th North of the Center 11. Found a boulder at the 1/16th South of the Center 11.

9-1-1978 County Surveyor dug at the 1/16th South of the Center 11 and found Hunter's stone .5' South and .75' West of the boulder found. Also dug at the Center 11 but could find nothing.

9-1978 County Surveyor searched for Armstrong's iron at the property corner East but found nothing.

9-5-1978 County Surveyor dug at a point on line and at Hunter's prorated measure from the 1/16th North of the Center 11 over the 1/16th South of the Center 11 but did not find anything. The corner comes in a cultivated field. Set a 1"x32" drill steel at this location.

9-28-1978 County Surveyor set a CIM over the iron set 9-5-1978.

3-21-2011 County survey crew found CIM in good condition.