Certificate of Location of Government Corner

ID#: 521109 **Description:** SEC CEN 11 52 **Date Set:** **County:** Olmsted

Section: 11 **Township:** 105N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

5-22-1877 Thomas Hunter, County Surveyor, (Book A, Page 311, Survey No. 305 & Old Field Book #5, Page 7) set 3"x6"/10"x16" stone at intersecting quarter lines. 1/16th North set 6"x9"x17" stone midway and on line at 20.08 chains (1325.28') to North 1/4. 1/16th South set 6"x7"x30" stone midway and on line at 19.94-1/2 chains (1316.37') to South 1/4. 1/16th Center of NE 1/4 set stake midway and on line at 19.93-1/2 chains (1315.71') on east-west sixteenth line. 1/16th Center of SW 1/4 set stake midway and on line at 19.92 chains (1314.72') on east-west sixteenth line. 1/16th Center of SE 1/4 set 3"x5"x20" stone midway and on line at 19.96 chains (1317.36') on east-west sixteenth line. RP - 3"x7"x15" stone N 25 links (16.50').

8-28-1978 County Surveyor probed around corner post. Found broken-up limestone, wood pieces, and wire loop 4' west of corner post and 0.6' south of the fence west. 1/16th North found Hunter's recorded stone up 0.5' in good condition. The stone falls 2-1/2' east and 4-1/2' south of corner post to fences east and south. 1/16th South found 8"x10"x16" boulder 3' south and 1' west of corner post.

8-29-1978 County Surveyor 1/16th Center of SE 1/4 searched for stone but did not find it. Found witness stone set 25 links (16.50') north. Witness stone falls 1' east of fence north and 3' west of 24" Burr Oak.

9-1-1978 County Surveyor dug and found nothing. 1/16th South found Hunter's stone 0.50' south and 0.75' west of boulder down 0.3'. Set 1"x16" conduit on east side of stone. The stone falls 1-1/2' west of fence north and 2-1/2' south of fence west. RP - CSD in East side corner post NE 3.85'

12-19-2006 GGG used computed center at intersecting quarter lines.