Certificate of Location of Government Corner

ID#:521204 **Description:** 1/4 SEC COR 12 13 52 **Date Set:** 10/8/1976 **County:** Olmsted

Section: 12 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.9'
County Survey Disk in W side 13" Most Southerly Burr Oak N 167.55'
County Survey Disk in top of brace post SW 127.85'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 12 and 13. 40.025 chs. Set quarter section post. Burr Oak 7" S61ºE 99 lks. Burr Oak 9" N21ºE 205 lks.

3-1857 H. Horton (P. 82 No. 123), a surveyor, used the corner.

5-1875 Thomas Hunter (P. 277 No. 274), County Surveyor, states that corner was gone and the remaining bearing tree did not agree by either course or measure with the location of the corner by measurement. Therefore, he disregarded the bearing tree and set a stone 4"x4"/11"x16" as the corner midway and on line from the N.E. Cor. Sec. 13 to the N.W. Cor. Sec. 13.

5-1903 Charles Armstrong (P. 50B), County Surveyor, found the stone 1' West of a corner post.

10-8-1976 County Surveyor dug in an open field and found the recorded stone 12" deep. Removed the stone and set a CIM over a 1/2"x2' rod 1.1'. North and .4' East at the midway and on line location by electronic traverse computation from the N.E. Cor. Sec. 13 to the N.W. Cor. Sec. 13.

3-18-2011 County survey crew found CIM in good condition.