Certificate of Location of Government Corner

ID#:521205 **Description:** SEC COR 11 12 13 14 52 **Date Set:** 10/6/1976 **County:** Olmsted

Section: 12 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.7'
The corner falls 1' north of centerline of CR 137 and 18 1/2' east of fence NE
County Survey Disk in Brace post NE 44.30'
County Survey Disk in PP 42.01'
This corner is located by GPS measurement.

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 13 and 14. 80.00 chs. Set post corner to sections 11-12-13-14. Burr Oak 7 in. S221/2ºW 473 lks. Burr Oak 8 in. S51/2ºW 669 lks. Set stone at corner and dug trench.

5-1875 Thomas Hunter (P. 277 No. 274), County Surveyor, found the remains of the old stake. Set a 4"x11"x20" stone in its place.

5-1877 T. Hunter (P. 311) found stone P. 277.

5-1903 Charles Armstrong (P. 50B) set a 4"x14"x16" stone in the center of the E-W road midway between the 1/16th North and the 1/16th South and on line from a stone found at the 1/16th South of 1/4 corner 13-14 over a stone found at the 1/16th North of 1/4 corner 13-14.

10-6-1976 County Surveyor dug and found a 4"x131/2"x18" stone lying flat over Hunter's recorded stone 41/2' deep with the stake hole beneath. Set the other stone over Hunter's stone and set a CIM over a 3/8"x8" iron over all.

10-22-1991 county highway department took ties as corner may be destroyed by bridge construction.

9-1-1992 County Surveyor found CIM in good condition.

1-6-2000 County Surveyor found CIM in good condition down 0.8'.

7-15-2009 County Surveyor found CIM down 0.6' in good condition.

2-24-2011 County survey crew found CIM in good condition.