Certificate of Location of Government Corner

ID#: 521209 **Description:** SEC CEN 12 52 **Date Set:** **County:** Olmsted

Section: 12 **Township:** 105N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

2-28-1867 H.E. Horton, County Surveyor, (Book A, Page 82, Survey No. 123) used corner at intersecting quarter lines. 1/16th North used midway and on line at 20.08 chains (1325.28') to North 1/4. 1/16th South used midway and on line at 20.06 chains (1323.96'). 1/16th East used midway and on line at 20.10 chains (1326.60') to East 1/4. 1/16th West used midway and on line at 19.94 chains (1316.04') to West 1/4. RP - Tree S20°W 67 links (44.22'). He also computed 1/16th Centers in all quadrants at intersecting sixteenth lines.

5-7-1903 Charles Armstrong, County Surveyor, (Book B, Pages 50-51) found stone. 1/16th South found stone at 20.03 chains (1321.98') then 20.07 chains (1324.62') to South 1/4.

8-9-1988 County Survey Crew dug and found nothing. 1/16th North dug and found nothing. 1/16th South dug and probed for stone found by Charles Armstrong and found nothing.

12-19-2006 GGG used computed center at intersecting quarter lines.

12-11-2012 G-Cubed used computed center at intersecting quarter lines.

8-13-2014 G-Cubed used computed center at intersecting quarter lines.