Certificate of Location of Government Corner

ID#:521304 **Description:** 1/4 SEC COR 13 24 52 **Date Set:** 9/28/1976 **County:** Olmsted

Section: 13 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.1'
The corner falls in line with fence north and 2' south of E-W fence
County Survey Disk in E side CP to fences E-W-N N 2.63'
County Survey Disk in S side most westerly of triple 13" Burr Oak E 30.11'
County Survey Disk in NW side 18" Burr Oak SSW 15.85'
County Survey Disk in W side blazed 7" Burr Oak S 40.65'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 13 and 14. 39.88 chs. Set quarter section post. White Oak 4 in. N30ºW 111 lks. Burr Oak 8 in. S40ºE 110 lks.

5-1875 Thomas Hunter (P. 277 No. 274), County Surveyor, states that the corner was gone and there was no evidence or knowledge of the corner. Set a stone 3"x11"x36" as the corner midway and on line.

4-1878 T. Hunter (P. 336 No. 330) found stone P. 277.

9-28-1976 County Surveyor found a 3"x11"x36" stone. Set a C.I.M. over a 1/2"x10" rod as the corner with the stone (broken in 3 pieces) on the South side of the C.I.M.

3-25-2011 County survey crew found CIM in good condition.