Certificate of Location of Government Corner

ID#:521306 **Description:** 1/4 SEC COR 13 14 52 **Date Set:** 10/21/1976 **County:** Olmsted

Section: 13 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.7'
The corner falls 293' east of centerline of CR 137 and 17 1/2' south of E-W fence
SW Corner shed (fdn) N 248.95'
County Survey Disk in S side PP #17074 W 265.9' (slope)
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 13 and 14. 32.80 chs. Brook 5 lks. wide runs S.W. 40.00 chs. Set quarter section post. Burr Oak 7 in. S36ºW 80 lks. Burr Oak 6 in. S72ºE 352 lks.

5-1875 Thomas Hunter (P. 277 No. 274), County Surveyor, states corner and both bearing trees gone. Set a 2"x8"x21" stone midway and on line as the corner. Set the 1/16ths North and South.

5-1903 Charles Armstrong (P. 50B) set a stone as the corner after finding stones as the 1/16ths North and South.

10-5&20-1976 County Surveyor dug for the corner with the backhoe but did not find anything.

10-21-1976 County Surveyor set a CIM over a 1/2"x2' rod as the corner midway and on line.

3-18-2011 County survey crew found CIM in good condition.