Certificate of Location of Government Corner

ID#:521405 **Description:** SEC COR 14 15 22 23 52 **Date Set:** 9/27/1978 **County:** Olmsted

Section: 14 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in NW side CP SW 29.16'
Post w/sign 2' SW
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 22 and 23. 80.00 chs. Set post corner to sections 14-15-22-23. Burr Oak 12 in. S531/2ºE 425 lks. Burr Oak 5 in. N49&3/4ºW 273 lks. Burr Oak 10 in. N72ºE 784 lks.

5-1877 Thomas Hunter (Book A. P. 313 No. 307), County Surveyor, states that the corner was gone. He set a 7"x10"x16" boulder from the stumps of the N.W. and S.E. bearing trees. Set stakes at the 1/16th South and the 1/16th East.

5-1893 William Fraser (Book A P. 506 No 476), County Surveyor, found boulder as recorded by Hunter.

5-1903 C. Armstrong (P.48 Book B) found a boulder 7"x12"x16" 2' North of the old fence row. Took B.O. 6 S89º30'E 87 lks. dist. mkd. T105, R12W, S23 B.T.

10-1904 C. Armstrong (P.74 Book B) found "a 6"x6"x10" granite boulder above gound with stake beside marked with 2 notches on E. and 3' on S. and witnessed by W.O. S89º30'E 87 lks." He set an iron stake 1"x1/2"x30" long at the 1/16th East midway and on line to 1/4 Cor. 23-24 which he reset this survey with a 1/2"x6' long iron.

9-19-1941 John Kerr (Kerr Book 26 P. 6), County Surveyor, states: "set 1" galv. angle iron at Cor. Sec. 14-15-22&23 with rock piled around it. Dug hole 2.5' square and filled with rock & raised them 10" above surface." Kerr gives no explanation of his method for setting this corner but shows it 2640' North of the corner post at 1/4 Cor. 22-23 1315.1' West of the 1/16th Cor. E. and 5253.5' E. of the S.W. Cor. Sec. 15.

4-1966 John Kerr found the corner set in 1941.

8&9-1978 County Surveyor found 1/4 Cor. 22-23 and 1/4 Cor. 14-23 (Hunter's corner, not Armstrong's reset corner). At the 1/16th East we found Armstrong's iron and possibly the mark from Hunter's stake 3' east. Dug at Section Cor. 14-15-22-23 and found a square mark in clay 2' deep with a stake hole on the N.W. side. The mark came at double the line and measure from 1/4 Cor.22-23 over the corner post at the 1/16th North and on line from 1/4 Cor. 14-23 over the mark (and also Armstrong's iron) and the 1/16th West. The mark at the 1/16th East would be just .6' from midway.

9-27-1978 County Surveyor set a Cast Iron Cap on a 4' long square pipe as the corner 6.9' East of Kerr's corner (removed.)

Correction of a Corner: The correct corner is 6.9' East of Kerr's corner (removed)

5-7-2002 County Surveyor found CIC up 1.1' in good condition. Set survey marker sign & post 2.0' SW.