Certificate of Location of Government Corner

ID#:521406 **Description:** 1/4 SEC COR 14 15 52 **Date Set:** 9/28/1978 **County:** Olmsted

Section: 14 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls approx. 400' SW of the intersection of CSAH 7 and TH 52

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 14 and 15. 40.00 chs. Set post for quarter section corner. Made mound and dug trench and pits and planted plum seeds N.S.E.W.

5-1903 C. Armstrong (P. 50 Book B) used a point midway (and probably on line) as the corner but does not say if he set anything here.

9-1941 John Kerr (Kerr Book P. 5) set a 1" pipe down 1' in open field midway and on line between the section corners after setting Sec. Cor. 14-15-22-23.

9-15-1967 John Kerr (certificate filed) set a CIM over a 3/4"x12" rod in place of the pipe set in 1941.

9-6-1978 County Surveyor found that Kerr errored in 1941 and his monument at 1/4 Cor. 14-15 was not on line and he did not have the correct corner at Sec. Cor. 14-15-22-23. Dug at the midway and on line location but did not find anything.

9-28-1978 County Surveyor set a CIM over a 1/2"x20" iron as the corner midway and on line 16.12' East and .27' North of Kerr's CIM (removed).

4-1-2002 County Surveyor found CIM down 0.8' in good condition.