Certificate of Location of Government Corner

ID#:521504 **Description:** 1/4 SEC COR 15 22 52 **Date Set:** 10/16/1978 **County:** Olmsted

Section: 15 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is at the surface
The corner falls under E-W fence
County Survey Disk in N side post on east side of huge CP E 8.24'
Post w/sign 0.5' west
This corner is located by GPS measurement

Corner History:

10-1853 Gov't. Notes William A. Jones, Deputy Surveyor West on true line between sections 15 and 22. 39.92 chs. Set quarter section post. Red Oak 6 in. S111/2ºE 72 lks. Red Oak 6 in. N25ºE 64 lks.

5-1893 William Fraser (Book A P. 506 No. 476), County Surveyor, states that the corner was gone but a Mr. F.G. Leske avers the corner came under the fence running E and W. Found a stake set by Hunter at the 1/16th East in an early day. Set a stake as the corner on line from Sec. Cor. 14-15-22-23 over Hunter's stake at the 1/16th and midway between the section corners. The corner came under the E-W fence. Set stones at the 1/16th South, the Center 22, the 1/16th South of the Center 22, the S 1/4 Cor. 22, and a property corner 22.30' & 7/8 chs. West of the Center 22 and the West 1/4 Cor. 22

5-31-1973 County Surveyor found Fraser's stone at the 1/16th South and a rectangular shaped mark with limestone chips at the Center 22 which was possibly Fraser's corner location.

11-1976 County Surveyor dug at the 1/16th South of the Center 22 and the S. 1/4 Cor. 22 but did not find anything.

5-25-1977 County Surveyor found Fraser's stones at the property corner 22.30' & 7/8 chs. West of the Center 22 and at the W. 1/4 Cor. 22. The mark found at the Center 22 in 1973 agreed with the line from the W. 1/4 Cor. 22 over the property corner found.

8-21-1978 County Surveyor dug for 1/4 Cor. 15-22 but did not find anything.

10-16-1978 County Surveyor set a Cast Iron Cap on a square pipe as the corner at double the line and measure of the mark found at the Center 22 and the stone at the 1/16th North in 1973. The corner came 1' North of the E-W fence.

3-7-2011 County survey crew found cast iron cap on square pipe in good condition.