Certificate of Location of Government Corner

ID#:521505 **Description:** SEC COR 15 16 21 22 52 **Date Set:** 10/31/1995 **County:** Olmsted

Section: 15 **Township:** 105N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 1' west of centerline of CSAH 7 and in line with fence east
County Survey Disk in N side PP #16696 SE 40.48'
Corner Orion Townhall SE 118.66'
County Survey Disk in E side TP SW 71.02'
Ref pipe E 44.23'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 21 and 22. 80.00 chs. Set post corner to sections 15-16-21-22. Burr Oak 8" N88ºW 345 lks. Burr Oak 8" S15ºW 161 lks. Burr Oak 7" N26ºE 176 lks. Burr Oak 6" S37ºE 98 lks. Burr Oak 12" N5ºE - -

5-1893 William Fraser (Book A P.506 No. 476), County Surveyor, states that the corner was gone. A Mr. F.G. Leska avers that the corner lays exactly in line with the fence East and the center of the road. The stump of the N.E. bearing tree placed the corner in the same place. He set a stone at the corner and a stake at the 1/16th South midway and on line to a stone he set a 1/4 Cor. 21-22.

1939 County Highway Department (C.H.D. Book 105) found a limestone.

1941 County Highway Department (C.H.D. Book 127 P. 40) records a 3/4" iron at the location of the limestone after the road was graded.

10-1948 John Kerr (Kerr Book 40 P. 27), County Surveyor, found the corner.

1962 J. Kerr (Kerr Book 85 P. 60-certificate filed) records a 3/4" iron at the corner. R.P.'s: Center of 3" Burr Oak S. of E. 54.25' S.W. Cor. of Orion Town Hall S.E. 118.6'.

5-25-1975 County Surveyor dug in line with the fence East and in the centerline of the N-S road on the recorded tie to the Orion Town Hall. Found 2' of crushed rock on clean clay. The area had been completely cut out. Dug at the 1/16th South and found a 5/8" square by 23" long iron with a nut on one end and an eyelet at the other. Dug at 1/4 Cor. 21-22 and found Fraser's recorded stone.

8-15-1978 County Surveyor set a CIM over a R.R. spike as Sec. Cor. 15-16-21-22 at double the line and measure from 1/4 Cor. 21-22 over the 1/16th North, both found in 1977. The corner is in line with the main line of the fence East, 1' West of the centerline of the N-S road and agrees with the tie to the Orion Townhall recorded in 1962. There is a Burr Oak of about 4" diameter and along side a small stump standing 54.0' E.S.E. of the CIM and is probably the location of the tree recorded by Kerr in 1962.

6-21-1995 County Surveyor found CIM. Referenced corner before cold recycling project on CR 7.

10-31-1995 county highway department set 1" square pipe w/cap.

12-10-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.