Certificate of Location of Government Corner

ID#:521604 **Description:** 1/4 SEC COR 16 21 52 **Date Set:** 4/21/1980 **County:** Olmsted

Section: 16 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is at the surface
The corner falls 1' east of fence north and 4' north of E-W fence
Center 12" Burr Oak N 7.7'
Nail in 4" Cedar NE 14.89'
County Survey Disk in 8" Blazed Burr Oak SW 15.27'
County Survey Disk in 10" Blazed Burr Oak SW 19.76'
County Survey Disk in 16" Blazed (dead) Burr Oak SSW 42.08'
Post w/sign 1' west
This corner is located by GPS reference stations

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 16 and 21. 40.15 chs. Set quarter section post. Bur Oak 7 in. N21ºE 60 lks. Bur Oak 7 in. S15ºW 79 lks. 80.30 chs. To section corner. Found no further survey records of this corner.

4-21-1980 County Surveyor set a 2' long square pipe with a Cast Iron Cap as the corner. The corner is set E-W in line with the main line of the fence North. The corner post at the 1/16th North fits well with this location and is just 1.5' West of the N-S 1/4 line. The corner is set N-S midway between a point at the projection of the line from the S.W. Cor. 16 over the fence East at the 1/16 East (which came 2.5' South) and a point at double the measure from the computed Center 16 over the fence West at the 1/16 South (which came 2.5' North). The corner is 3' North of the E-W fence and 1' East of the fence North at the corner of the fences N-E-W. Dug at the location the monument is set but did not find anything. The ground was frozen and the dirt very shallow to rock.

7-22-2011 County survey crew found cast iron cap on square pipe in good condition.