Certificate of Location of Government Corner

ID#:521605 **Description:** SEC COR 16 17 20 21 52 **Date Set:** 10/25/1976 **County:** Olmsted

Section: 16 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fence south and 3 1/2' north of fence east
County Survey Disk in NW side 10" Cedar NE 42.2'
This corner is located by GPS reference stations "521605 B & C"

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 20 and 21. 80.00 chs. Set post corner to sections 16,17,20 & 21 Red Oak 12 in. N61ºW 20 lks. Burr Oak 15 in. N31ºE 63 lks. Burr Oak 12 in. S61ºE 63 lks.

6-1894 William Fraser (P. 546 No. 506), County Surveyor, found the corner post to be the corner after testing with the SW, NE and NW bearing trees. Set a 3"x8"x23" stone on the North side of the corner post.

6-1902 Robert Fraser (P. 710 No. 624), County Surveyor, found the stone P. 546.

10-25-1976 County Surveyor found the remaining 12" of William Fraser's stone over a hole (with wood pieces) chiseled in bedrock. Set a CIM over a 1/2"x8" rod as the corner with the stone on the south side and a disc coulter between the CIM and the stone.

7-21-2009 County Surveyor found CIM down 0.5' in good condition. Set post w/sign.