Certificate of Location of Government Corner

ID#:521606 **Description:** 1/4 SEC COR 16 17 52 **Date Set:** 4/1/1977 **County:** Olmsted

Section: 16 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.5'
The corner falls under N-S fence
County Survey Disk in E side PP with transformer NNE 283.8'
County Survey Disk in W side fence post NW 181.5'
Post with sign 2' south
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 16 and 17. 40.00 chs. Set quarter section post. Red Oak 5 in. S50ºE 80 lks. Red Oak 5 in. S62ºW 12 lks.

1879 Thomas Hunter, County Surveyor, (Field Book 5 p. 94) used the 1/4 post. Measure North for 11/2 miles.

6-1891 Thomas Fraser, County Surveyor, (P. 452 No. 436) found the marked stake. Measured North 2 miles to 1/4 Cor. 4-5 and set Sec. Cor. 8-9-16-17 North-South at 1/4 this distance.

6-1902 Robert Fraser, County Surveyor, (P. 710 No. 624) states that the corner is now in a plowed field. Set a stone as the corner midway and on line between the section corners.

4-1-1977 County Surveyor found a 3"x12"x18" stone down 1' in a cultivated field. Dug the stone down and set a C.I.M. over a 1/2" x 2' rod as the corner.

2-23-2011 County survey crew found CIM in good condition.