Certificate of Location of Government Corner

ID#:521705 **Description:** SEC COR 17 18 19 20 52 **Date Set:** 4/19/1977 **County:** Olmsted

Section: 17 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is at the surface
The corner falls 1/2' NE of CP and in line with fences E-W-S
Spike in E side huge Maple N 19.93'
County Survey Disk in S side blazed 18" Maple NE 37.00'
County Survey Disk in NW side 16" blazed Maple SW 42.70'
Post with sign 1' north
This corner is located by GPS reference stations

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 19 and 20. 80.00 chs. Set post-corner to sections 17-18-19-20. Sugar Maple 8 in. S45ºE15 lks. Sugar Maple 10 in. S57ºW 91/2 lks. Ash 16 in. N89ºW 23 lks. Sugar Maple 10 in. N--E 35 lks.

11-1856 Thomas Hunter, County Surveyor, (P. 17 No. 27) used the corner to set the 1/16th West.

6-1857 Thomas Hunter (P. 32 No. 50) measured East to 1/4 Cor. 17-20. Set property corners between Sec. Cor. 17-18-19-20 and 1/4 Cor. 17-20.

6-1857 T. Hunter (P. 32 No. 51) used the corner to set the 1/16th West.

6-1902 Robert Fraser (P. 710 No. 624) found the corner. Set the 1/4 cor. 17-18 midway and on line between the section corners.

4-1977 County Surveyor dug around the corner post but did not find anything.

4-19-1977 County Surveyor set a Cast Iron Cap on a square pipe as the corner on the N.E. side of the old corner post to fences E-W-S.

7-19-2011 County survey crew found cast iron cap on square pipe in good condition.