Certificate of Location of Government Corner

ID#:521804 **Description:** 1/4 SEC COR 18 19 52 **Date Set:** 4/19/1977 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1/2' north of CP and in line with fences N-W-S
County Survey Disk in NW side large blazed Red Oak SW 37.89'
Spike in W side 17" Oak S 39.95'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor East on true line between sections 18 and 19. 39.87 chs. Set quarter section post. White Oak 26 in. S20ºE 53 lks. Hickory 5 in. N16ºE 35 lks. 79.87 chs. To section corner.

11-1856 Thomas Hunter, County Surveyor, (P. 17 No. 27) used the corner to set the 1/16th East.

6-1857 Thomas Hunter, County Surveyor, (P. 32 No. 51) used the corner to the 1/64th East and the 1/16th East.

approx.1900 H.S. Gillman (Field Book 12 P. 20) records a stone at the corner and at the 1/16th East.

4-19-1977 County Surveyor dug around the corner post and also at the 1/16th East but did not find anything. Set a Cast Iron Cap on a square pipe on the North side of the corner posr as the corner and in line with fences N-W-S. The corner is also 0.3' south of a large pipe also driven on the North side of the corner post.

7-15-2011 County survey crew found cast iron cap up 0.3' in good condition