Certificate of Location of Government Corner

ID#:521805 **Description:** W SEC COR 18 19 52 **Date Set:** 5/15/1973 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road, 18' NW of centerline of twp road on curve and 12' south of centerline of farm driveway west
Punch mark in N end 15" CMP SSE 47.1'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor North between sections 19 and 24. 80.00 chs. Set section corner post. Blk. Oak 10 in. N40 degrees E 13 lks. Aspen 8 in. S 2 degrees E 4 lks. Blk. Oak 12 in. S 60 degrees W 18 lks. Burr Oak 6 in. N 20 degrees W 54 lks.

9-1885 Thomas Hunter (P.403 No.392), County Surveyor, states SE bearing tree and stump (marked) of SW bearing tree still standing. Found old stake remains and set a long limestone with stake by its side.

6-1894 William Fraser (P.546 No.506), County Surveyor found stone.

5-15-1973 County Surveyor found recorded limestone 3.5' deep. Set CIM over a 3/4"x8" iron over the stone.

1-7-2008 County Surveyor found CIM down 0.5' in good condition.

7-10-2009 County Surveyor found CIM down 0.5' in good condition.