Certificate of Location of Government Corner

ID#:522004 **Description:** 1/4 SEC COR 20 29 52 **Date Set:** 7/7/2009 **County:** Olmsted

Section: 20 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 0.6' NE of CP
Post w/sign 1 1/2' ESE
This corner is located by GPS measurement

Corner History:

10-6-1853 Gov't Notes W on true line between section 20 & 29 VAR 10º30'E 39.95 Set qr. section post Aspen 4N33W 14 4" N33°W 14 lks. Cherry 5S14W17 5" S14°W 17 lks. To section corner 79.90

9-1879 T. Hunter P. 363 No. 354 Found marked stake by post of fence. Bearing trees gone.

6-7-1894 W. Fraser P. 546 No. 506 Found stake P.363 - set stone 2"x8"x25" in place of stake. 1/16 W drove stake M&L 20.02 chs. 1/16 E set stone 2"x10"x25" M&L 19.93 chs. 1/16 N. drove stake M&L 19.94 chs. Set stakes north dividing 19.94 into 5 plots.

4-1901 W. Fraser P. 2B found stone at corner post of fence.

5-18-1973 County Surveyor found recorded limestone .6 NE of TP (very pointed and quite long). Drove small irons on E&W sides of stone.

12-28-1999 GGG found and used limestone as corner for survey in NW 1/4 sec 29.

7-7-2009 County Surveyor found stone up 0.5' in good condition. Took ties and removed. Set 4' telspar pipe w/Cast Iron Cap up 0.3' at stone location. Set post w/sign ESE 1 1/2'.