Certificate of Location of Government Corner

ID#:522204 **Description:** 1/4 SEC COR 22 27 52 **Date Set:** 10/3/1978 **County:** Olmsted

Section: 22 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' south of E-W fence and in line with fence north
County Survey Disk in SE side 17" Red Oak NE 41.28'
County Survey Disk in S side 14" Black Oak WNW 18.40'
County Survey Disk in N side blazed 21" Red Oak ENE 41.87'
This corner is located by GPS reference stations.

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor West between sections 22 and 27. 40.00 chs. Set post for quarter section corner. Deposited handful charcoal, made mound, dug trench & pits, planted cherry seeds NE & SW No trees near. 80.00 chs. To section corner.

5-1893 William Fraser (Book A P. 506 No. 476), County Surveyor, found the stake in mound. Set a limestone at the 1/16th North, the Center 22, and the 1/16th North of the Center 22. He set stakes at the 1/16th West and the 1/64th West of the 1/16th West. He also set a stone at a property corner 22.30 & 7/8 chs. West of the Center 22.

10-1901 William Fraser (Book B P. 25) found the stake at the 1/16th West set P. 506.

5-1973 County Surveyor found Fraser's stone at the 1/16th North of the Center 22 and found a rectangular mark with limestone chips at the Center 22 believed to be the location of Fraser's stone.

11-24-1976 County Surveyor doubled the line and measure from the mark found at the Center 22 in 1973 over a long limestone on the South side of the corner post at the 1/16th South (being used as a dead man for a brace) and dug for the corner but did not find anything. Measured West to the SW Cor. 22.

5-25-1977 County Surveyor found Fraser's property corner 20.30 & 7/8 chs. West of the Center 22 and found the W. 1/4 Cor. 22. The mark found at the Center 22 in 1973 came on line from the W. 1/4 Cor. 22 over the property corner.

10-3-1978 County Surveyor dug at the 1/16th North but did not find anything further. Dug further at 1/4 Cor. 22-27 but did not find anything. Set a CIM over a 1/2" x 2' rod as the corner on line from the 1/16th North of the Center 22 over the mark found at the Center 22 and at double the measure from the mark at the Center 22 over the 1/16th fence South. The corner came 1 1/2' South of the corner post to the fences E-W-N.

7-21-2011 County survey crew found cast iron monument in good condition