Certificate of Location of Government Corner

ID#:522206 **Description:** 1/4 SEC COR 21 22 52 **Date Set:** 9/20/1995 **County:** Olmsted

Section: 22 **Township:** 105N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 7' west of centerline of CSAH 7
County Survey Disk in S side TP NW 36.66'
County Survey Disk in N side PP #16777 NE 72.40'
County Survey Disk in S side PP #16778 SE 59.60'
Ref pipe NW 36.17'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 21 and 22. 40.00 chs. Set quarter section post. Red Oak 6 in. S571/2ºW 85 lks. Red Oak 6 in. N68ºE 92 lks.

5-1893 William Fraser (Book A P.506 No. 476), County Surveyor, found a stake in the center of the road. Also found the NE witness tree and the SW witness tree stump. The corner was 2 rods West of the cemetary fence and on line with it running East. Set a 5"x12"x20" stone with the stake by its side.

10-29-1948 John Kerr (Kerr Book 40 P. 27), County Surveyor, records a 1" pipe at this corner.

5-25-1977 County Surveyor dug and found Fraser's recorded stone with a stake on the East side 4' deep in the road. Set a 1"x22" pipe in the stake hole. Set a 1/2"x2' rod at the road surface over the stone. The corner is .5' North and 1.35' East of the pipe recorded by Kerr.

8-15-1978 County Surveyor removed the 1/2" rod set in 1977 and set a CIM over a drag tooth as the corner.

6-21-1995 County Surveyor found CIM in good condition. Tied out corner for overlays.

9-20-1995 County Surveyor set 1" square pipe w/cap at surface.

1-11-2008 County Surveyor found 1" square pipe w/cap at surface in good condition. Did not update ties.