Certificate of Location of Government Corner

ID#:522305 **Description:** SEC COR 22 23 26 27 52 **Date Set:** 10/16/1978 **County:** Olmsted

Section: 23 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls on the south edge of field drive west and in line with fence west.
County Survey Disk in E side PP #16808 NW 50.97'
County Survey Disk in N side huge gate post NE 57.08'
County Survey Disk in W side PP #16809 SSE 37.14'
Post w/sign 6' SE
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 26 and 27. 80.00 chs. Set post corner to sections 22-23-26-27. Burr Oak 16 in. S171/2ºE 555 lks. Burr Oak 12 in. N89ºE 220 lks. Dug trench.

5-1877 Thomas Hunter (Book A. P. 312 No. 306), County Surveyor, states that the corner was gone. Reset a marked stake from the 2 bearing trees standing. Set a stake at the 1/16th East.

5-1877 Hunter (Book A P. 313 No. 307) found the stake P. 312. Set a stake at the 1/16th North.

10-11-1978 County Surveyor dug over a large area both with the backhoe and by hand but could find nothing. The area had been cut to clay in the construction of the road.

10-16-1978 County Surveyor set a C.I.M. over a 1/2"x22" iron as the corner at double the measure from 1/4 Cor. 23-26 (set this survey) over a 4 1/2"x6"/9"x16" limestone found by the corner post at the 1/16th West and in line with the fence West. This location brought the fence at the 1/16th North midway.

5-6-2002 County Surveyor found CIM down 0.6' in good condition. Set sign & post 6' SE.