Certificate of Location of Government Corner

ID#:522404 **Description:** 1/4 SEC COR 24 25 52 **Date Set:** 6/13/1973 **County:** Olmsted

Section: 24 **Township:** 105N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is at the surface
The monument is 1.5' north of corner post for fences N and W
State Reference Point in fence post N 6.06'
Spike in 36" Burr Oak of original gov't. Bearing tree SW 82.32'
This corner is located by GPS measurement.

Corner History:

10-6-1853 Gov't Notes West on true line between sections 24&25. VAR 10°10'E 40.00 Set qr. section post Burr Oak 5"S 361/2W 125 (Bearing tree still here on June 13, 1973) 80.00 To section corner.

4-1878 T. Hunter P. 336 No. 330 Corner gone - one witness tree still standing (did not agree anywhere near midway). 1/16 east & west set stakes M&L 19.911/3. Bearings E - N89°55E W S89°15W shows kink. 16 center NE1/4 25 set stake M&L on N-S 1/16 line M&L 20.03 3/4.

6-13-1973 County Surveyor ran electronic traverse to within 100' of corner post of fences running N & W - Found original gov't bearing tree. Tree well over 3' dia. In perfect shape & condition, about 81' from ctr. Tree to corner post Set CIM over iron at 82.5' from center tree & midway on no. line sect. 25. Corner comes about 1.65' NNE of center new corner post.

7-13-1977 Mn/DOT Survey Crew found CIM and took 3 new references.

2-11-2011 County survey crew found CIM in good condition